

# Solenoid coil MSW-230AC-60-OD

Part number: 34408

FESTO



## Data sheet

| Feature                                      | Value                                                     |
|----------------------------------------------|-----------------------------------------------------------|
| Type of actuation                            | Electric                                                  |
| Mounting position                            | optional                                                  |
| Min. pick-up time                            | 10 ms                                                     |
| Duty cycle                                   | 100%                                                      |
| Insulation material class                    | F                                                         |
| Characteristic coil data                     | 220 V AC: 60 Hz, pick-up power 36 VA, holding power 28 VA |
| Permissible voltage fluctuations             | +/- 10 %                                                  |
| CE mark (see declaration of conformity)      | To EU Low Voltage Directive                               |
| UKCA marking (see declaration of conformity) | To UK regulations for electrical equipment                |
| LABS (PWIS) conformity                       | VDMA24364-C1-L                                            |
| Storage temperature                          | -10 °C...60 °C                                            |
| Degree of protection                         | IP65                                                      |
| Ambient temperature                          | -5 °C...50 °C                                             |
| Product weight                               | 150 g                                                     |
| Electrical connection                        | Type A<br>Plugs<br>To EN 175301-803                       |
| Type of mounting                             | External hex 1/8<br>Retaining clip                        |
| Note on materials                            | RoHS-compliant                                            |
| Material solenoid coil                       | Duroplast                                                 |
| Material electrical contact                  | Brass, tin-plated                                         |
| Material winding                             | Copper                                                    |