

Fine filter LFMB-3/8-D-MINI-DA

Part number: 532819

FESTO



Data sheet

| Feature | Value |
|---|---|
| Series | D |
| Size | Mini |
| Design | Fibre filter |
| Grade of filtration | 1 µm |
| Condensate drain | Manually rotating |
| Operating pressure | 0.1 MPa...1.6 MPa 1 bar...16 bar 14.5 psi...232 psi |
| Operating medium | Compressed air to ISO 8573-1:2010 [6:4:4] Inert gases |
| Air purity class at output | Compressed air to ISO 8573-1:2010 [5:4:3] Inert gases |
| Max. standard flow rate for clean air class | 675 l/min |
| Min. standard flow rate for clean air class | 125 l/min |
| Filter efficiency | 99.99 % |
| Max. condensate volume | 22 cm ³ |
| Bowl guard | Metal bowl guard |
| Corrosion resistance class CRC | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Media temperature | 1.5 °C...60 °C |
| Ambient temperature | -10 °C...60 °C |
| Storage temperature | -10 °C...60 °C |
| Filter efficiency, fine particles | 99 % |
| Residual oil content | 0.5 mg/m ³ |
| Filter efficiency, oil aerosol | 90 % |
| Differential pressure display | Visual display |
| Type of mounting | Either: In-line installation With accessories |
| Mounting position | Vertical +/-5° |
| Pneumatic connection, port 1 | G3/8 |

| Feature | Value |
|------------------------------|--------------------|
| Pneumatic connection, port 2 | G3/8 |
| Material housing | Die-cast zinc |
| Material filter | Borosilicate fibre |
| Material bowl | PC |
| Note on materials | RoHS-compliant |
| Product weight | 368 g |