
Pressure regulator
MS12-LR-G-PO

Part number: 541680





Data sheet

Feature	Value
Size	12
Series	MS
Mounting position	optional
Design	Diaphragm regulator
Controller function	Output pressure constant Via primary pressure compensation With secondary venting With return flow function
Pressure gauge (ANALOG) or Pressure display (DIGITAL)	With pressure gauge
Operating pressure	0.08 MPa...2.1 MPa 0.8 bar...21 bar
Pressure regulation range	0.5 bar...16 bar
Max. pressure hysteresis	0.04 MPa 0.4 bar 5.8 psi
Flow rate of secondary exhaust	600 l/min
Standard nominal flow rate (standardised to DIN 1343)	13000 l/min...22000 l/min
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4] Inert gases
Corrosion resistance class CRC	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Storage temperature	-10 °C...60 °C
Media temperature	-10 °C...60 °C
Ambient temperature	-10 °C...60 °C
Product weight	4000 g
Type of mounting	Either: In-line installation Via mounting bracket
Pilot air port 12	G1/4
Pneumatic connection, port 1	Sub-base
Pneumatic connection, port 2	Sub-base
Material covering	PA
Note on materials	RoHS-compliant

Feature	Value
Material underneath cover	Wrought aluminium alloy
Material seals	NBR
Material spring	Spring steel
Material housing	Die-cast aluminium
Material membrane	NBR
Material valve stem	Wrought aluminium alloy NBR High-alloy stainless steel