



# Solenoid valve

## VUVG-L10A-M52-RZT-M3-1P3

FESTO

Part number: 566443



## Data sheet

| Feature   | Value   |
|---|---|
| Valve function  | 5/2-way, monostable   |
| Type of actuation                                     | Electric  |
| Valve size  | 10 mm   |
| Standard nominal flow rate (standardised to DIN 1343) | 100 l/min   |
| pneumatic working port                                | M3  |
| Operating voltage                                     | 24V DC  |
| Operating pressure                                    | -0.09 MPa...1 MPa<br>-0.9 bar...10 bar  |
| Design  | Piston gate valve   |
| Type of reset   | Mechanical spring<br>Pneumatic spring   |
| Approval  | RCM trademark<br>c UL us - Recognized (OL)  |
| CE mark (see declaration of conformity)               | To EU EMC Directive<br>To EU Low Voltage Directive<br>In accordance with EU RoHS Directive          |
| UKCA marking (see declaration of conformity)          | To UK instructions for EMC<br>To UK RoHS instructions<br>To UK regulations for electrical equipment |
| Degree of protection                                  | IP40<br>IP65<br>With plug socket  |
| Nominal size  | 2 mm  |
| Exhaust-air function                                  | With flow control option  |
| Sealing principle                                     | Soft  |
| Mounting position                                     | optional  |
| Manual override                                       | Detenting<br>Non-detenting<br>Covered   |
| Type of piloting                                      | Pilot actuated  |
| Pilot air supply                                      | External  |
| lap   | Overlap   |
| Pilot pressure  | 0.25 MPa...0.8 MPa<br>2.5 bar...8 bar   |
| Suitability for vacuum                                | yes   |

| Feature   | Value  |
|---|--|
| Switching time off  | 15 ms  |
| Switching time on   | 7 ms   |
| Duty cycle  | 100%   |
| Max. positive test pulse with 0 signal                    | 700 µs   |
| Max. negative test pulse with 1 signal                    | 900 µs   |
| Characteristic coil data                                  | 24 V DC: 1.0 W<br>24 V DC: low-current phase 0.3 W, high-current phase 1.0 W               |
| Permissible voltage fluctuations                          | +/- 10 %   |
| Operating medium  | Compressed air to ISO 8573-1:2010 [7:4:4]  |
| Note on operating and pilot medium                        | Lubricated operation possible (in which case lubricated operation will always be required) |
| Vibration resistance                                      | Transport application test with severity level 2 to FN 942017-4 and EN 60068-2-6           |
| Restrictions for environmental and media temperature      | -5 ... 50° C<br>Without holding current reduction  |
| Shock resistance  | Shock test with severity level 2 to FN 942017-5 and EN 60068-2-27                          |
| Corrosion resistance class CRC                            | 2 - Moderate corrosion stress  |
| LABS (PWIS) conformity                                    | VDMA24364-B1/B2-L  |
| Cleanroom suitability, measured according to ISO 14644-14 | Class 5 according to ISO 14644-1   |
| Media temperature   | -5 °C...60 °C  |
| Pilot medium  | Compressed air to ISO 8573-1:2010 [7:4:4]  |
| Ambient temperature                                       | -5 °C...60 °C  |
| Product weight  | 38 g   |
| Electrical connection                                     | Via electrical sub-base  |
| Type of mounting  | Either:<br>On manifold rail<br>With through-hole   |
| Pilot air port 12/14                                      | M3   |
| Pneumatic connection, port 1                              | M3   |
| Pneumatic connection, port 2                              | M3   |
| Pneumatic connection, port 3                              | M3   |
| Pneumatic connection, port 4                              | M3   |
| Pneumatic connection, port 5                              | M3   |
| Note on materials   | RoHS-compliant   |
| Material seals  | HNBR<br>NBR  |
| Material housing  | Wrought aluminium alloy  |