

Electric cylinder ESBF-BS-40-100-16P

Part number: 8022581

FESTO



Data sheet

| Feature | Value |
|--------------------------------------|--|
| Working stroke | 100 mm |
| Size | 40 |
| Stroke | 100 mm |
| Piston rod thread | M12x1.25 |
| Reversing backlash theoretical | 40 µm |
| Spindle diameter | 16 mm |
| Spindle pitch | 16 mm/U |
| Torsional backlash at piston rod +/- | 0.2 deg |
| Based on standard | ISO 15552 |
| Mounting position | optional |
| Piston-rod end | Male thread |
| Type of motor | Stepper motor Servo motor |
| Position detection | Via proximity switch |
| Design | Electric cylinder with ball screw |
| Spindle type | Ball screw |
| Protection against torque/guide | With plain-bearing guide |
| Max. acceleration | 25 m/s ² |
| Max. rotational speed | 4800 rpm |
| Max. speed | 1.33 m/s |
| Repetition accuracy | ±0.01 mm |
| Duty cycle | 100% |
| Corrosion resistance class CRC | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364 zone III |
| Storage temperature | -20 °C...60 °C |
| Suitable for use with food | See supplementary material information |
| Relative air humidity | 0 - 95% |
| Degree of protection | IP40 |
| Ambient temperature | 0 °C...60 °C |
| Max. drive torque | 7.7 Nm |
| Max. radial force at drive shaft | 130 N |
| Max. feed force Fx | 3000 N |

| Feature | Value |
|--|--|
| Frictional torque independent of load | 0.2 Nm |
| Reference value effective load, horizontal | 300 kg |
| Reference value effective load, vertical | 300 kg |
| Mass moment of inertia JH per metre of stroke | 0.5225 kgcm ² |
| Mass moment of inertia JL per kg of working load | 0.06485 kgcm ² |
| Mass moment of inertia JO | 0.1249 kgcm ² |
| Maintenance interval | Life-time lubrication |
| Moving mass for 0 mm stroke | 467 g |
| Additional moving mass per 10 mm stroke | 26 g |
| Basic weight for 0 mm stroke | 1237 g |
| Additional weight per 10 mm stroke | 47 g |
| Type of mounting | Via female thread Or accessories |
| Interface code, actuator | D40 |
| Note on materials | RoHS-compliant |
| Material cover | Wrought aluminium alloy, smooth anodised |
| Material piston rod | High-alloy stainless steel |
| Material screws | Galvanised steel |
| Material ball screw nut | Rolled steel |
| Material spindle | Rolled steel |
| Material cylinder barrel | Smooth-anodised wrought aluminium alloy |