


# Proportional directional control valve

## VPWS-6-B-6-PC15-3-V

FESTO

Part number: 8074537



## Data sheet

Feature	Value
Nominal size	6 mm
Type of actuation	Electric
Sealing principle	Soft
Mounting position	optional
Design	Directly actuated poppet valve
Type of reset	Mechanical spring
Type of piloting	Direct
Flow direction	Non-reversible
Valve function	2/2 proportional directional control valve, closed
Operating pressure	0 MPa...0.3 MPa 0 bar...3 bar
Nominal operating pressure	0.3 MPa 3 bar 43.5 psi
Burst pressure	1.5 MPa 15 bar 217.5 psi
Standard flow rate (standardised to DIN 1343)	200 l/min...230 l/min
Hysteresis	22.5 mA
Switching time on	10 ms
Current regulating range	0 mA...225 mA
Max. electrical power consumption	3 W
Coil resistance R20	60.5 Ohm
Duty cycle	100% (see operating instructions)
Frequency PWM control	3 kHz
Voltage PWM control	24 V
Note on PWM control	The permissible current range must not be exceeded when using pulse-width modulation.
Oxygen suitability according to standard	ISO 15001
Biocompatibility according to standard	ISO 18562
Maximum impurity level for hydrocarbons	550 MGM
Vibration resistance	Transport application test with severity level 1 to FN 942017-4 and EN 60068-2-6

Feature	Value
Note on vibration resistance	Oscillation in the Z direction can lead to fluctuations in the flow rate
Shock resistance	Shock test with severity level 1 to FN 942017-5 and EN 60068-2-27
Note on shock resistance	A shock in the Z-direction can lead to fluctuations in the flow rate
Corrosion resistance class CRC	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364 zone III
Medium	Inert gases Air Oxygen
Note on the medium	Lubricated operation not possible Maximum particle size 10 µm
Media temperature	5 °C...50 °C
Degree of protection	IP60
Note on degree of protection	IP65 with suitable plug In assembled state
Ambient temperature	5 °C...50 °C
Storage temperature	-40 °C...80 °C
Product weight	25 g
Electrical connection 1, connection type	Cable
Electrical connection 1, connector system	Open end
Electrical connection 1, number of connections/cores	2
Cable length	70 mm...80 mm
Type of mounting	On sub-base Plug-in With accessories
Pneumatic connection, port 1	Cartridge 7.5 mm
Pneumatic connection, port 2	Cartridge 15 mm
Note on materials	RoHS-compliant
Material seals	FPM
Material housing	High-alloy steel