

# T822K1034

THERMOSTAT – LOW VOLTAGE / 24 V



24 V



This model can be installed in homes as well as in commercial premises. Its settings make it possible to control up to five relays without transformers or one relay with a transformer.

- **COMPATIBLE WITH ALL RE, RM AND R841 RELAYS**
- **CAN CONTROL UP TO 5 RELAYS**
- **TEMPERATURE IN DEGREES CELSIUS**

#### COLOUR

- white

#### VOLTAGE

- 1.2 A @ 24 Vac

#### CONTROL

- two-wire connection
- all or nothing (on/off) @ 24 Vac
- compatible with all RE, RM and R841 model relays
- can control up to 5 relays
- temperature in degrees Celsius

#### TEMPERATURE RANGE

- 10 to 30 °C (50 to 86 °F)

#### WARRANTY

- one year

## TECHNICAL SPECIFICATIONS

PRODUCT	DESCRIPTION
T822K1034	low voltage thermostat (24 V)

DIMENSIONS: 2.83 in. x 4.75 in. x 1.46 in. (71.9 mm x 120.7 mm x 37.1 mm)

°STELPRO

Stelpro reserves the right to modify at any time the description, manufacturing, or price of its products. Additionally, Stelpro may apply restocking fees or refuse a refund based on one or more of the following criteria: optional color, custom product, assembly with low-demand options. For the latest product information and prices regarding the products, please visit the website [www.stelpro.com](http://www.stelpro.com).