


Copper C-Taps

Type CCT

- Manufactured from high conductivity copper alloy
- Used for making tap or parallel copper connections
- Provides consistent reliability with heavy wall construction that prevents relaxation of the joint after installation
- Installation time is reduced because of its "C" shape



| CATALOG NUMBER | CONDUCTOR RANGE | | APPROXIMATE DIMENSIONS (IN.) | | | WIRE STRIP LENGTH | INSTALLATION TOOLING | | |
|----------------|---------------------|---------------------|------------------------------|------|------|-------------------|----------------------|-----------|---------------|
| | RUN | TAP | L | H | W | | PENN-UNION TOOL | DIE INDEX | NO. OF CRIMPS |
| CCT-46 | 6 Sol. - 4 Str. | 6 Sol. - 6 Str. | .63 | .75 | .44 | 3/4" | TPU-12B | BG | 1 |
| CCT-44 | 6 Sol. - 4 Str. | 4 Sol. - 4 Str. | .63 | .81 | .44 | 3/4" | | BG | |
| CCT-24 | 2 Sol. - 2 Str. | 8 Sol. - 4 Str. | .75 | 1.00 | .63 | 7/8" | | C | |
| CCT-22 | 2 Sol. - 2 Str. | 2 Sol. - 2 Str. | .75 | 1.00 | .63 | 7/8" | | C | |
| CCT-2020 | 1/0 Str. - 2/0 Str. | 1/0 Str. - 2/0 Str. | .94 | 1.38 | .81 | 5/8" | | O | |
| CCT-4020 | 3/0 Str. - 4/0 Str. | 1/0 Str. - 2/0 Str. | 1.06 | 1.63 | 1.00 | 13/16" | | D3 | |
| CCT-4040 | 3/0 Str. - 4/0 Str. | 3/0 Str. - 4/0 Str. | 1.06 | 1.56 | 1.00 | 13/16" | | D3 | |

F