

## KCB2B2B2B0000V0WZ (Order no. 078855)

### Series KC...

- ▶ Screw terminal
- ▶ 4 actuating directions
- ▶ Interlocking in switch position 0 (V0)
- ▶ Bellows for panel mounting (W)
- ▶ Center-position switch (Z)



## Technical data

### Approvals



### Electrical connection values

Fuse	T6/F10
Rated insulation voltage $U_i$	250 V
Rated impulse voltage $U_{imp}$	2.5 kV
Utilization category	AC-15 230V 4A DC-13 24V 2A
Switching voltage	min. 10 V
Switching current	(at 24V) min. 12 mA

### Mechanical values and environment

Connection type	Screw terminal
Number of monitoring contacts	max. 9 8 + 1 (4 directions x 2 switching elements and 1x Z contact)
Actuating directions	max. 4 max. 3 positions (0-1-2) possible per type and direction
Storage temperature	-25 ... 70 °C
Mechanical life	1 x 10 <sup>6</sup>
Center-position switch	1 changeover contact (NO contact closed, NC contact open in neutral position (not actuated))
Mounting cut-out	Ø 52 mm
Switching principle	Changeover contact C, IEC 947-5-1 (Snap-action contact element, design ES556)
Degree of protection	on the front with bellows IP65 (Version W)

Ambient temperature                      -5 ... 65 °C

**Material**

Contact	Silver alloy
	Switching lever galvanized steel
	Housing thermoplastic/aluminum
	Bellows elastomer, black (Low PAH)

**Miscellaneous****Additional feature**

Interlocking in center position
Bellows W for panel mounting