

## KFT1234R (Order no. 028449)

### Series KF...

- ▶ Control panel installation at rear
- ▶ 1 to 8 actuating directions, 4 switching elements.  
Stayput switch, spring return switch or combined
- ▶ One changeover contact with screw terminal for each actuating direction
- ▶ Center-position switch



## Technical data

### Approvals



### Electrical connection values

Fuse	T10/F20
Rated insulation voltage $U_i$	250 V
Rated impulse voltage $U_{imp}$	2.5 kV
Utilization category	AC-15 230V 5A DC-13 24V 3A
Switching voltage	min. 12 V
Switching current	(at 24V) min. 10 mA

### Mechanical values and environment

Connection type	Screw terminal
Number of monitoring contacts	4 (4 directions)
Actuating directions	4 (Pushbutton)
Storage temperature	-25 ... 70 °C
Mechanical life	1 x 10 <sup>6</sup>
Mounting cut-out	D22 (EN IEC 60947-5-1)
Switching principle	Changeover contact C, IEC 947-5-1 (Snap-action contact element, design ES517A)
Degree of protection	on the front with bellows IP65
Ambient temperature	-25 ... 65 °C

## Material

Bellows elastomer, black  
(Low PAH)

Switching lever stainless steel

Housing thermoplastic/duroplast

Contact Silver alloy

## Miscellaneous

Additional feature

All-round actuation