


TP3-4141C024MC1844 (Order no. 096896)

Technical data

Approvals



Electrical connection values

Fuse	max. 4 A gG
Power consumption	8 W
Rated insulation voltage U_i	250 V
Rated impulse voltage U_{imp}	2.5 kV
Utilization category	
	DC-13 4 A 24 V
	AC-15 4 A 230 V
Solenoid operating voltage	
	AC/DC 24 V -15% ... +10%
Solenoid duty cycle	100 %
Switching voltage	
	min. at 10 mA 12 V
Switching current	
	min. at 24 V 1 mA
thermal rated current I_{th}	4 A

Mechanical values and environment

Anfahrsgeschwindigkeit	max. 20 m/min
Connection type	
	3 x M20 x 1.5
Number of door position positively driven contacts	2
Number of guard lock monitoring positively driven contacts	2
Extraction force	20 N
Actuation frequency	max. 1200 1/h

Actuating force	10 N
Installation orientation	any
Storage temperature	-25 ... 70 °C
Mechanical life	1 x 10 ⁶
Retention force	10 N
Switching principle	Slow-action switching contact
Degree of protection	IP67
Ambient temperature	-20 ... 55 °C
Material	
	Housing Reinforced thermoplastic
	Contact Silver alloy, gold flashed
Locking force F _{max}	1300 N
Locking force F _{Zh}	1000 N
Guard locking principle	Closed-circuit current principle

Characteristic values according to EN ISO 13849-1 and EN IEC 62061

	B10 _D	Mission time
Monitoring of the guard position	3x10 ⁶	20 y
	Important! Values valid at DC-13 100 mA/24V	
Guard lock monitoring	3x10 ⁶	20 y
	Important! Values valid at DC-13 100 mA/24V	

	PL	Maximum SIL	Category	Mission time
Control of guard locking	Depending on external control of guard locking			20 y

Miscellaneous

C number	C1844 with identical locking
----------	------------------------------