

RIEGEL CET-A-C-C2308 (Order no. 109672)

Bolt for safety switch CET

- ▶ Bolt for switch family CET
- ▶ Steel bolt
- ▶ For doors hinged on the left or right
- ▶ Without door stop
- ▶ Suitable for a door gap of 15 mm



Scope of delivery

- ▶ Cover AM-C-124721 for actuator CET

To be ordered separately:

- ▶ Safety switch CET / read head CET.-AX
- ▶ Actuator CET

Door types and door hinges

Suitable for hinged or sliding doors. Suitable for doors hinged on the left or right. Without door stop, door can be opened inwards and outwards.

Cover

With the cover AM-C-124721, tampering on the CET is effectively prevented. The cover prevents the use of simple tools to manually press up the spring-mounted guard locking pin on the actuator.

Integrated lockout bar

With the aid of the integrated lockout bar, the bolt can be secured in the open position, e.g. using padlocks. It is possible to prevent people from being locked in the danger area unintentionally.

Technical data

Mechanical values and environment

Approach direction	A or C
Number of safety switches that can be mounted	1
Escape release	None
Storage temperature	-25 ... 70 °C
Material	
Handle	Plastic
Base plate	Galvanized steel
Guide strips	Plastic
Switch bracket	Steel powder-coated

Miscellaneous

C number	
C2308	Bolt without door stop
Detent mechanism	None