# MGB–L2HB–PNA–R–113134 (Order no. 113134)

Locking set MGB–L2…–PN… (guard locking by solenoid force) with 6 controls and indicators, push–pull plug

- ▸ Guard locking with guard lock monitoring
- ▸ Emergency stop according to ISO 13850 (illuminated)
- ▸ 2 illuminated pushbuttons
- ▸ 2 pushbutton, not illuminated
- ▸ 1 indicator
- ▸ Including adhesive labels
- ▸ Push–pull plug
- ▸ Pre–assembled on mounting plates
- ▸ Integrated Profinet RT switch
- ▸ Unicode

Profinet connection

Connection via push–pull plugs according to IEC 61076–3–117

Profinet RT switch

Point–to–point topology network structure due to integrated RT switch.

Flexible use as interlocking or guard locking

By means of the corresponding evaluation of the safe device data by the control system, use can be as either interlocking or guard locking (with or without monitoring).

Emergency stop illuminated

Emergency stop with illumination that can be controlled as required.

Dimensional drawings

Components

106049

MGB-H-AA1A2-R-106049

Handle module MGB-H-...

▸ Intelligent bolt tongue
▸ Lockout mechanism
▸ Door handle
▸ Mounting plate

113133

MGB-L2B-PNA-R-113133

Evaluation module and bus module MGB-L2...-PN... (guard locking by solenoid force) with 6 controls and indicators, push-pull plug

▸ Guard locking with guard lock monitoring
▸ Emergency stop according to ISO 13850 (illuminated)
▸ 2 illuminated pushbuttons
▸ 2 pushbutton, not illuminated
▸ 1 indicator
▸ Including adhesive labels
▸ Push-pull plug
▸ Pre-assembled on mounting plates
▸ Integrated Profinet RT switch
▸ Unicode