

STM1A-222D024-M (Order no. 115323)

Technical data

Approvals



Electrical connection values

Fuse	max. 4 A gG
Power consumption	6 W
Connection cross section	0.34 ... 1.5 mm ²
Rated insulation voltage U_i	250 V
Rated impulse voltage U_{imp}	2.5 kV
Utilization category	
	DC-13 4 A 24 V
	AC-15 4 A 230 V
Solenoid operating voltage	
	AC/DC 24 V -15% ... +10%
Solenoid duty cycle	100 %
Switching voltage	
	min. at 10 mA 12 V
Switching current	
	min. at 24 V 1 mA
thermal rated current I_{th}	4 A

Mechanical values and environment

Anfahrsgeschwindigkeit	max. 20 m/min
Approach direction	D
Connection type	
	1 x M20 x 1.5
Number of door position positively driven contacts	2
Number of guard lock monitoring positively driven contacts	1

Extraction force	30 N
Actuation frequency	max. 1200 1/h
Actuating force	35 N
Installation orientation	any
Insertion depth	24.5 mm
Storage temperature	–25 ... 70 °C
Mechanical life	2 x 10 ⁶
Retention force	20 N
Switching principle	Slow-action switching contact
Degree of protection	IP67
Ambient temperature	–20 ... 55 °C
Material	
Contact	Silver alloy, gold flashed
Housing	Reinforced thermoplastic
Locking force $F_{\max}$	2000 N
Locking force F_{Zh}	1500 N
Guard locking principle	Closed-circuit current principle

Characteristic values according to EN ISO 13849–1 and EN IEC 62061

	B10 _D	Mission time
Monitoring of the guard position	2x10 ⁶	20 y
	Important! Values valid at DC–13 100 mA/24V	
Guard lock monitoring	2x10 ⁶	20 y
	Important! Values valid at DC–13 100 mA/24V	

	PL	Maximum SIL	Category	Mission time
Control of guard locking	Depending on external control of guard locking			20 y