

WKT2/4W (Order no. 028525)

Series WK...

- ▶ Control panel installation according to IEC 947-5-1 D30
- ▶ Pushbutton with two actuating directions
- ▶ Two changeover contacts with tab connector 2.8 x 0.5 IEC 760 for each actuating direction
- ▶ Bellows



Technical data

Approvals



Electrical connection values

Fuse	T6/F10
Rated insulation voltage U_i	250 V
Rated impulse voltage U_{imp}	2.5 kV
Utilization category	
	DC-13 24V 2A
	AC-15 230V 4A
Switching voltage	min. 10 V
Switching current	
	(at 24V) min. 12 mA

Mechanical values and environment

Connection type	Tab connector 2.8x0.5 IEC760
Number of monitoring contacts	4 (2 directions)
Actuating directions	2 (Pushbutton)
Storage temperature	-25 ... 70 °C
Mechanical life	1 x 10 ⁶
Mounting cut-out	D30 (EN IEC 60947-5-1)
Switching principle	Changeover contact C, IEC 947-5-1 (Snap-action contact element, design ES584)
Degree of protection	
	on the front with bellows IP65
Ambient temperature	-5 ... 65 °C

Material

	Bellows elastomer, black (Low PAH)
Contact	Silver alloy
	Housing thermoplastic/aluminum
	Switching lever stainless steel

Miscellaneous

Additional feature	Bellows
--------------------	---------