

NM03VZB-M (Order no. 085575)

Technical data

Approvals



Electrical connection values

Fuse	max. 4 A gG
Connection cross section	0.34 ... 1.5 mm ²
Rated insulation voltage U _i	250 V
Rated impulse voltage U _{imp}	2.5 kV
Utilization category	
	AC-15 4 A 230 V
	DC-13 4 A 24 V

Switching voltage

min. at 10 mA 12 V

Switching current

min. at 24 V 1 mA

thermal rated current I_{th} 4 A

Mechanical values and environment

Anfahrsgeschwindigkeit	max. 20 m/min
Approach direction	B
Connection type	
	3 x M16 x 1.5
Number of door position positively driven contacts	3
Extraction force	10 N
Design	long housing
Actuation frequency	max. 7000 1/h
Actuating force	10 N
Installation orientation	any
Insertion depth	20 mm

Storage temperature	-25 ... 80 °C
Mechanical life	1 x 10 ⁶
Retention force	2 N
Switching principle	Slow-action switching contact
Degree of protection	IP67
Ambient temperature	-20 ... 80 °C
Material	
	Housing Reinforced thermoplastic
	Contact Silver alloy, gold flashed

Characteristic values according to EN ISO 13849-1 and EN IEC 62061

	B10 _D	Mission time
Monitoring of the guard position	4x10 ⁶	20 y
Important! Values valid at DC-13 100 mA/24V		

In combination with actuator ACTUATOR-M-G

Overtravel	4 mm
------------	------