

RPS3131SC175RSFM5 (Order no. 111492)

Rope pull switch with pull-to-reset button for EMERGENCY STOP device, clamping head, plug connector M12

- ▶ Plastic housing
- ▶ Emergency stop device with detent mechanism as per EN ISO 13850 and EN 60947-5-5
- ▶ Clamping head for pull wire
- ▶ Indication of correct rope tension
- ▶ Plug connector M12, 5-pin, right
- ▶ Switching elements with 2 switching contacts
- ▶ Emergency stop




Switching element

3131 Slow-action switching contact 2 NC (→)

Technical data

Approvals



Electrical connection values

Fuse	max. 4 A gG
Rated insulation voltage U_i	50 V
Rated impulse voltage U_{imp}	1.5 kV
Utilization category	AC-15 3 A 50 V
Switching current	at 24V min. 10 mA
Safety class	II
thermal rated current I_{th}	4 A

Mechanical values and environment

Connection type	Plug connector M12 (5-pin (without PE) - right)
Number of positively driven contacts	2
Actuating force	175 N
Installation orientation	any
Storage temperature	-25 ... 70 °C
Mechanical life	0.1 x 10 ⁶
Switching principle	Slow-action switching contact
Degree of protection	IP67
Rope diameter	2 ... 5 mm
Ambient temperature	-25 ... 70 °C
Material	Housing Reinforced thermoplastic

Characteristic values according to EN ISO 13849-1 and EN IEC 62061

	B10 _D	Mission time
Emergency stop	0.1x10 ⁶	20 y

Miscellaneous

Additional feature

Emergency stop function