

SLE-LED

Linear Striplight

Experience ultimate convenience and performance with RAB DESIGN's re-imagined SLE Strip Light. Featuring an elegant, toolless opening, universal adjustable settings, and high lumen output, this fixture is engineered to give contractors the best installation experience. Available in three lengths, with and without sensor, and optional Bluetooth controls.

IDEAL APPLICATIONS

- ✔ Retail Applications

✔ Office Spaces
- ✔ Parkades

✔ Warehouse Aisles
- ✔ Commercial Applications

✔ General Indoor Lighting
- ✔ Stairwell & Hallway

✔ Storage spaces

SPECIFICATIONS

	SLE2-LED25A15	SLE4-LED50A30	SLE8-LED80A60	SLE8-LED100A60		SLE2-LED25A15	SLE4-LED50A30	SLE8-LED80A60	SLE8-LED100A60
PERFORMANCE					AMBIENT OPERATING TEMPERATURE				
Light Output	Lumen Selectable				-35°C to 45°C (-31°F to 113°F)				
	3600/ 2900/ 2200 lm	7300/ 5800/ 4400 lm	13000/ 11000/ 9500 lm	17300/ 13900 / 10400 lm					
Efficacy	147 lm/W	137 lm/W	156 lm/W	177 lm/W	MOUNTING				
CCT	3000/3500/4000/5000K (Selectable)			3500/4000/ 5000K (Selectable)	Surface Mount Suspension Mount (Kit Sold Separately)				
					CERTIFICATIONS				
					cULus Listed for Canada and USA, per UL 1598, CSA C22.2 No. 250.0 DLC Standard & Premium				
Beam Angle	130°			130°	CONTROLS				
Replaces up to	2 LAMP F21T5	2 LAMP T5HO	4 LAMP 28WT5	4 LAMP T8	Dimming	0-10V (Dim to Off)			
CRI	85	85	84	83		5-100% Dimming		10-100% Dimming	5-100% Dimming
ELECTRICAL					Sensor	Dimming High Frequency Microwave Motion Sensor with Remote Control Bluetooth PIR Motion & Daylight Harvest Sensor			
Wattage	25/20/15W	50/40/30W	80/70/60W	100/80/60W		LUMEN MAINTENANCE			
Voltage	120-347 V					L90	51,000 Hrs	63,000 Hrs	51,000 Hrs
Power Factor	>0.99				L85	76,000 Hrs	97,000 Hrs	76,000 Hrs	94,000 Hrs
THD	9%	2%	3%	7%	L70	>100,000 Hrs	>100,000 Hrs	>100,000 Hrs	>100,000 Hrs
Daisy Chain	Max 22 fixtures at 120V and 62 fixtures at 347V	Max 11 fixtures at 120V and 31 fixtures at 347V	Max 7 fixtures at 120V and 19 fixtures at 347V	Max 5 fixtures at 120V and 15 fixtures at 347V	MAX AMPERAGE DRAW (A)				
Battery Backup	-	8W (Optional)			120V	0.231	0.463	0.741	0.926
CONSTRUCTION					208V	0.134	0.267	0.427	0.534
Housing	Steel Sheet Metal				240V	0.116	0.231	0.370	0.463
Paint	White Powder Coat Finish				277V	0.100	0.201	0.321	0.401
Lens	Frosted Polycarbonate				347V	0.080	0.160	0.256	0.320
Weight	2.21 lbs	3.86 lbs	7.28 lbs		Note: Electrical and light performance data is based on LM79 test reports, measured at maximum wattage, 4000K, and 120V.				

Note: Electrical and light performance data is based on LM79 test reports, measured at maximum wattage, 4000K, and 120V.

Life hours are derived from IESNA LM-80 testing report and projected per IESNA TM-21 calculations.

CONTROLLED

ORDERING GUIDE

Fixture	Wattage	Voltage	Colour Temp.	Dimming	Controls	Battery Backup
SLE2	LED25A15	H - 120-347V	VK - Colour Selectable ¹	DIM - 0-10V Dimming	Blank - No Controls	Blank - No Battery Backup
SLE4	LED50A30				DHFS - Dimming High Frequency Microwave Motion Sensor	BBK8- 8W Battery Backup ²
SLE8	LED80A60 LED100A60					

¹SLE2, SLE4 and SLE8-LED80A60 are CCT selectable between 3000/3500/4000/5000K. SLE8-LED100A60 is CCT selectable between 3500/4000/5000K.

²Offered with SLE4 and SLE8 only.


Default Setting: Maximum Wattage and 4000K

STOCK CODE		INCLUDED IN THE BOX	
099955	SLE2-LED25A15-H-VK-DIM	Surface Mount Kit	
099956	SLE4-LED50A30-H-VK-DIM		
099957	SLE8-LED80A60-H-VK-DIM		
084491	SLE8-LED100A60-H-VK-DIM		
084095	SLE2-LED25A15-H-VK-DIM-DHFS	Junction Box Cover	
084096	SLE4-LED50A30-H-VK-DIM-DHFS		
084097	SLE8-LED80A60-H-VK-DIM-DHFS		
084570	SLE8-LED100A60-H-VK-DIM-DHFS		


ACCESSORIES SOLD SEPARATELY					
084138	SLE LOWBAY BLUETOOTH PIR MOTION/DLH SENSOR W/J-BOX ¹		084102	SLE4-LED REFLECTOR WINGS KIT - WHT	
084215	BLUETOOTH 3-KEY AC LINE VOLTAGE WALL SWITCH 120-277VAC, 3-KEYS (ON/OFF, DIM+, DIM-)		084135	SLE8-LED REFLECTOR WINGS KIT - WHT	
002412	SLE2-LED WIRE CAGE WHT		089814	LINEAR CEILING PENDANT MOUNT KIT (2x 5FT AIRCRAFT CABLES)	
002413	SLE4-LED WIRE CAGE WHT		087016	RC-100 MOTION SENSOR REMOTE CONTROL	
002414	SLE8-LED WIRE CAGE WHT		084136	SLE-LED ROW MOUNT KIT - WHT	

¹ Each sensor can control one fixture only.

SLE2-LED FIXTURE



SLE4-LED FIXTURE



SLE8-LED FIXTURE

