

KCA6A6A6A6A0000V0X (Order no. 030335)

Series KC...

- ▶ Tab connector 2.8 x 0.5
- ▶ 4 actuating directions
- ▶ Interlocking in switch position 0 (V0)
- ▶ Bellows for surface mounting (X)



Technical data

Approvals



Electrical connection values

Fuse	T6/F10
Rated insulation voltage U_i	250 V
Rated impulse voltage U_{imp}	2.5 kV
Utilization category	DC-13 24V 2A AC-15 230V 4A
Switching voltage	min. 10 V
Switching current	(at 24V) min. 12 mA

Mechanical values and environment

Connection type	Tab connector 2.8 x 0.5 IEC 760
Number of monitoring contacts	max. 12 12 (4 directions x 3 switching elements)
Actuating directions	max. 4 max. 3 positions (0-1-2) possible per type and direction
Storage temperature	-25 ... 70 °C
Mechanical life	1 x 10 ⁶
Mounting cut-out	Ø 52 mm
Switching principle	Changeover contact C, IEC 947-5-1 (Snap-action contact element, design ES556)
Degree of protection	on the front with bellows IP65 (Version X)
Ambient temperature	-5 ... 65 °C

Material

	Switching lever galvanized steel
Contact	Silver alloy
	Housing thermoplastic/aluminum
	Bellows elastomer, black (Low PAH)

Miscellaneous

Additional feature

- Interlocking in center position
- Bellows X for surface mounting