

N1AK502LE110-M (Order no. 087213)

Technical data

Approvals



Electrical connection values

Fuse	max. 8 A gG	
Connection cross section	0.34 ... 1.5 mm ²	
Display module	AC	93.5 ... 110 ... 126.5 V LED
Rated insulation voltage U_i	250 V	
Rated impulse voltage U_{imp}	2.5 kV	
Utilization category	AC-12	8 A 250 V
	DC-13	6 A 24 V
	AC-15	6 A 230 V

Switching current	min. at DC 12V	
	10 mA	
thermal rated current I_{th}	8 A	

Mechanical values and environment

Anfahrsgeschwindigkeit	0.01 ... 10 m/min	
Connection type	2 x	M16 x 1.5
Number NC contacts	1	
Number of switching elements	1	
Number of NO contacts	1	
Design	Housing according to DIN 43693	
Actuating element	Ball plunger	
Actuating force	min. 20 N	
Installation orientation	any	

Storage temperature	-25 ... 80 °C
Mechanical life	30 x 10 ⁶
Contact bounce time	max. 3 ms
Switching principle	Snap-action switching contact
Operating point accuracy	± 0,01 (The reproducible operating point accuracy refers to the axial travel of the plunger after the switching element ES 502 E has been run-in with approx. 2,000 operating cycles.)
Schließzeit	max. 4 ms
Degree of protection	IP67
Ambient temperature	-5 ... 80 °C
Material	

Housing	Anodized die-cast alloy
Contact	Silver alloy, gold flashed