

**TZ2RE024RC18VAB-C2070 (Order no. 094612)**

## Technical data

### Approvals



### Operating and display elements

LED display

Operating voltage corresponds to the solenoid voltage  
(2 LEDs; green, red)

### Electrical connection values

Fuse	max. 4 A gG (>70 °C =>2 A gG)	
Power consumption	10 W	
Rated insulation voltage $U_i$	50 V	
Rated impulse voltage $U_{imp}$	1.5 kV	
Utilization category		
	AC-15	4 A 50 V (>70 °C =>2 A)
	DC-13	4 A 24 V (>70 °C =>2 A)
Solenoid operating voltage	AC/DC	24 V -15% ... +10%
Solenoid duty cycle	100 %	
Switching voltage		
	min. at 10 mA	12 V
Switching current		
	min. at 24 V	1 mA
thermal rated current $I_{th}$	4 A (>70 °C =>2 A)	

### Mechanical values and environment

Anfahrsgeschwindigkeit	max. 20 m/min
------------------------	---------------

Approach direction

Actuating head on the right A

Connection type	
	1 x Plug connector RC18 (18 + PE)
Number of door position NO contacts	1
Number of guard lock monitoring NO contacts	1
Number of door position positively driven contacts	3
Number of guard lock monitoring positively driven contacts	2
Extraction force	30 N
Actuation frequency	max. 1200 1/h
Actuating force	35 N
Lid	black
Installation orientation	any
Insertion depth	52 mm
Storage temperature	-25 ... 80 °C
Mechanical life	1 x 10 <sup>6</sup>
Retention force	10 N
Switching principle	Slow-action switching contact
Degree of protection	IP65
Ambient temperature	-25 ... 80 °C
Material	
	Housing Anodized die-cast alloy
	Contact Silver alloy, gold flashed
Locking force $F_{max}$	2000 N
Locking force $F_{Zh}$	1500 N
Guard locking principle	Open-circuit current principle

## Characteristic values according to EN ISO 13849-1 and EN IEC 62061

	B10 <sub>D</sub>	Mission time
--	------------------	--------------