

## RIEGEL CET-A-C/F (Order no. 106172)

### Bolts for CET products

- ▶ Bolt for switch family CET with escape release
- ▶ Steel bolt
- ▶ For doors hinged on the left or right
- ▶ Bolt with escape lever
- ▶ Detent knob in open position
- ▶ Suitable for a door gap of approx. 15 mm



### Scope of delivery

- ▶ Bolt parts
- ▶ Cover AM-C-124721 for CET actuator

### To be ordered separately:

- ▶ Safety switch CET/read head CET.-AX
- ▶ CET actuator

### Latching in open position

Latching in the open position is intended to prevent persons from trapping themselves in a machine from the inside. The bolt slider is latched in the detent position. Unlock by pulling the detent knob upward.

### Escape release

Bolts with escape release feature an escape lever enabling the bolt to be opened from inside a guard.

### Door types and door hinges

Suitable for hinged or sliding doors. Suitable for doors hinged on the left and right. With door stop, door cannot be opened inwards.

### Cover

With the cover AM-C-124721, tampering on the CET is effectively prevented. The cover prevents the use of simple tools to manually press up the spring-mounted guard locking pin on the actuator.

### Integrated lockout bar

With the aid of the integrated lockout bar, the bolt can be secured in the open position, e.g. using padlocks. It is possible to prevent people from being locked in the danger area unintentionally.

## Technical data

### Mechanical values and environment

Approach direction	A or C
Number of safety switches that can be mounted	1
Escape release	Yes
Storage temperature	-25 ... 70 °C
Material	
Handle	Plastic
Guide strips	Plastic
Base plate	Galvanized steel
Switch bracket	Steel powder-coated

### Miscellaneous

Detent mechanism open position	Bolt detent mechanism
--------------------------------	-----------------------