

KCB2B2B2B0000DWZ (Order no. 070866)

Series KC...

- ▶ Screw terminal
- ▶ 4 actuating directions
- ▶ Pushbutton in handle (D)
- ▶ Bellows for panel mounting (W)
- ▶ Center-position switch (Z)



Technical data

Approvals



Electrical connection values

| | |
|---------------------------------|-------------------------------|
| Fuse | T6/F10 |
| Rated insulation voltage U_i | 250 V |
| Rated impulse voltage U_{imp} | 2.5 kV |
| Utilization category | AC-15 230V 4A DC-13 24V 2A |
| Switching voltage | min. 10 V |
| Switching current | (at 24V) min. 12 mA |

Pushbutton in handle

| | |
|----------------------|-------------------------------|
| Utilization category | AC-15 230V 2A DC-13 24V 1A |
| Switching voltage | min. 10 V |
| Switching current | (at 24V) min. 12 mA |

Mechanical values and environment

| | |
|-------------------------------|--|
| Connection type | Screw terminal |
| Number of monitoring contacts | max. 9 8 + 1 (4 directions x 2 switching elements and 1x Z contact) |
| Actuating directions | max. 4 max. 3 positions (0-1-2) possible per type and direction |
| Storage temperature | -25 ... 70 °C |
| Mechanical life | 1 x 10 ⁶ |

