

## WKS1234DVWZ (Order no. 027982)

### Series WK...

- ▶ Control panel installation according to IEC 947-5-1 D30
- ▶ Switch with actuating directions 1-4
- ▶ One changeover contact with tab connector 2.8 x 0.5 IEC 760 for each actuating direction
- ▶ Center-position switch
- ▶ Pushbutton in handle
- ▶ Bellows
- ▶ Interlocking in center position



## Technical data

### Approvals



### Electrical connection values

Fuse	T6/F10
Rated insulation voltage $U_i$	250 V
Rated impulse voltage $U_{imp}$	2.5 kV
Utilization category	DC-13 24V 2A AC-15 230V 4A
Switching voltage	min. 10 V
Switching current	(at 24V) min. 12 mA

### Pushbutton in handle

Test voltage	AC 1 kV
Switching voltage	DC 10 ... 50 V

### Mechanical values and environment

Connection type	Tab connector 2.8x0.5 IEC760
Number of monitoring contacts	4 + 1 (4 directions and Z contact)
Actuating directions	4 (Switch)
Storage temperature	-25 ... 70 °C
Mechanical life	1 x 10 <sup>6</sup>
Center-position switch	1 changeover contact (NO contact closed, NC contact open in neutral position (not actuated))
Mounting cut-out	D30 (EN IEC 60947-5-1)

