

NB01R620–MC2276/V100 (Order no. 102235)

Technical data

Approvals



Electrical connection values

Fuse	max. 6 A gG	
Connection cross section	0.14 ... 1 mm ² (Screw terminal)	
Rated insulation voltage U _i	250 V	
Rated impulse voltage U _{imp}	2.5 kV	
Utilization category	AC-15	2 A 230 V
	DC-13	2 A 24 V
Switching current	min. at DC 24V	10 mA
thermal rated current I _{th}	6 A	

Mechanical values and environment

Anfahrsgeschwindigkeit	0.01 ... 50 m/min	
Connection type	1 x	M12 x 1.5 (Special cable gland)
Number of door position NC contacts	1	(Changeover contact)
Number of door position NO contacts	1	(Changeover contact)
Actuating element	Slide bearing metal	Roller plunger (d roller = 5 mm)
Actuating force	15 ... 20 N	
Installation orientation	any	

Storage temperature	-25 ... 80 °C
Mechanical life	10 x 10 ⁶
Switching principle	Changeover contact with snap-action function
Degree of protection	IP67
Ambient temperature	-5 ... 80 °C
Material	
	Contact Silver alloy, gold flashed
	Housing Anodized die-cast alloy

Characteristic values according to EN ISO 13849-1 and EN IEC 62061

B _{10D}	20 x 10 ⁶
------------------	----------------------

Miscellaneous

C number	
	C2276
Additional feature	Packaging unit V100