

## WET1234DW (Order no. 018609)

### Series WE...

- ▶ Control panel installation at rear or with front plate
- ▶ Pushbutton with actuating directions 1-4
- ▶ One changeover contact with screw terminal for each actuating direction
- ▶ Bellows
- ▶ Pushbutton in handle



## Technical data

### Approvals



### Electrical connection values

Fuse	T16/F25
Rated insulation voltage $U_i$	250 V
Rated impulse voltage $U_{imp}$	2.5 kV
Utilization category	DC-13 24V 4A AC-15 230V 10A
Switching voltage	min. 24 V
Switching current	(at 24V) min. 50 mA

### Pushbutton in handle

Utilization category	AC-15 230V 2A DC-13 24V 1A
Switching voltage	min. 10 V
Switching current	(at 24V) min. 12 mA

### Mechanical values and environment

Connection type	Screw terminal
Number of monitoring contacts	4 (4 directions)
Actuating directions	4 (Pushbutton)
Storage temperature	-25 ... 70 °C
Mechanical life	1 x 10 <sup>6</sup>
Mounting cut-out	Ø 42 mm

Switching principle	Changeover contact ZA, IEC 947-5-1 (Snap-action contact element, design ES502V1)
---------------------	-------------------------------------------------------------------------------------

Degree of protection

on the front with bellows IP65

Ambient temperature	-5 ... 65 °C
---------------------	--------------

Material

Switching lever galvanized steel

Contact Silver alloy

Housing thermoplastic/aluminum

Bellows elastomer, black  
(Low PAH)

## Pushbutton in handle

Actuating force max. 8 N

Mechanical life

(at 0.7A / 250V AC) 0.05 x 10<sup>6</sup>

Switching principle 1 contact

## Miscellaneous

Additional feature

Pushbutton in handle

Bellows