

MGB2-L1HB-PN-U-S4-AA-R-165050 (Order no. 165050)

Components



137617

MGB2-H-BA1A1-R-137617

Handle module MGB2-H... (door handle, door hinge on right)

- ▶ Intelligent bolt tongue
- ▶ Fold-out lockout mechanism
- ▶ Door handle
- ▶ Adjustable door hinge; factory setting: right



165052

MGB2-L1-MLI-U-YA9G5-AA-R-165052

Locking module MGB2-L1-MLI... (4 pushbuttons, emergency stop, cover for indicators, closed-circuit current principle, door hinge on right)

- ▶ Guard locking for the protection of persons or processes
- ▶ Locking module MGB2 for connection to a bus module MBM
- ▶ Interlocking with monitored guard locking
- ▶ Category 4/PL e for the evaluation of all safety functions
- ▶ 1 emergency stop according to ISO 13850
- ▶ 4 illuminated pushbuttons
- ▶ 1 signal indicator
- ▶ Adjustable door hinge; factory setting: right
- ▶ Unicode
- ▶ Compatible with all Modular devices



156312

MBM-PN-S4-MLI-3B-156312

Bus module MBM-PN... (M12 connection, D-coded, Power 7/8")

- ▶ This item has been replaced by a new version and should not be used for new projects. We recommend the use of the new version MBM-PN-S4-MLI-3B-169765.
- ▶ For connecting MGB2 or MCM modules
- ▶ Connection to PROFINET with PROFI-safe
- ▶ Connection via plug connector M12, D-coded
- ▶ Remote or direct mounting
- ▶ Integrated switch
- ▶ Compatible with all Modular devices

Technical data

Handle modules MGB2-H-BA1A1-R-137617 (Order no. 137617)



Mechanical values and environment

Installation orientation	Door hinge DIN right
Storage temperature	-30 ... 70 °C
Degree of protection	IP65
Ambient temperature	-30 ... 55 °C
Material	
	Housing Fiber glass reinforced plastic, nickel-plated die-cast zinc, stainless steel

Locking modules MGB2-L1-MLI-U-YA9G5-AA-R-165052 (Order no. 165052)



Mechanical values and environment

Installation orientation	Door hinge DIN right
--------------------------	----------------------

Bus modules MBM-PN-S4-MLI-3B-156312 (Order no. 156312)



Electrical connection values

Connecting cable		
	MLI	5-pin, M12x1
Rated insulation voltage U_i		75 V
Rated impulse voltage U_{imp}		0.5 kV
EMC protection requirements		EMC Directive 2014/30/EU
maximum feed-in current in the connection block		
	XD1, XD2	max. 6000 mA
Safety class		III
Current consumption		max. 150 mA