

CMS-R-BZB-03V+CMS-M-BH (Order no. 124194)

Components



092025

CMS-M-BH

Actuator CMS design B

- ▶ Cube-shaped version, 36 x 26 mm



097368

CMS-R-BZB-03V

Read heads design B for ESM, PVC

- ▶ In combination with evaluation units ESM-BA...
- ▶ Cube-shaped version, 36 x 26 mm
- ▶ Connecting cable
- ▶ Cable type: PVC

Technical data

Approvals



Mechanical values and environment

Storage temperature -25 ... 70 °C



Actuator CMS-M-BH (Order no. 092025)

Mechanical values and environment

Tightening torque 0.4 ... 0.5 Nm

Design B

Storage temperature -25 ... 80 °C

Degree of protection IP67

Ambient temperature -20 ... 80 °C

Material

Housing PPS

Method of operation Magnetic

Miscellaneous

in compliance with EN ISO 13849-1:2015; EN 50178:1997; EN 60204-1:2006/A1:2009; EN ISO 14119:2013; EN 61000-6-2:2005; EN 61000-6-3:2007/A1:2011; EN 60947-5-3:2013



Read heads CMS-R-BZB-03V (Order no. 097368)

Electrical connection values

Fuse

Power supply / safety contacts, external contact protection Fuse 10 A gG
(Parameter dependent on the evaluation units ESM-BA2.. and ESM-BA3..)