


NZ2VZ-528E3VSM04L060 (Order no. 045856)

Safety switch NZ.VZ.VSM, plug connector M26 (SR6)

- ▶ Plug connector M26 (SR6)
- ▶ 1 pos. driven contact
- ▶ 1 NO contacts
- ▶ LED indicator
- ▶ Guard locking for process protection
- ▶ Closed-circuit current principle



Approach direction



Horizontal

Actuating head and solenoid can each be adjusted in 90° steps

Guard locking principle

Power to unlock: On a guard with guard locking based on the closed-circuit current principle, the guard is locked by spring force until the guard locking solenoid is supplied with power. Unlocking is by solenoid force. The term mechanical guard locking is also used.

LED indicator

The switch has a freely assignable LED indicator (red).

Switching element



528H Slow-action switching contact 1 positively driven contact $\bigcirc\rightarrow$ + 1 NO contact

Guard locking for process protection

The safety switch meets the requirements for interlocking devices with guard locking for process protection. It does not possess safe guard lock monitoring.

Accessories required


Actuator and solenoid plug are not included.

Functional drawings

511  21  22
528 13  14

21  22
13  14

Dimensional drawings



1) In the inserted and screwed tight state

- a Travel without operation: actuator is in the guide slot, but function is not triggered.
- b Switching operation completed: actuator must be inserted to this point to ensure safe switching. The actuator must be withdrawn at least to point a for switching off.