

NM11KBC–MC2069 (Order no. 103907)

Technical data

Approvals



Electrical connection values

Fuse	max. 4 A gG
Connection cross section	0.34 ... 1.5 mm ²
Rated insulation voltage U_i	250 V
Rated impulse voltage U_{imp}	2.5 kV
Utilization category	
	AC-15 4 A 230 V
	DC-13 4 A 24 V

Switching voltage

min. at 10 mA 12 V

Switching current

min. at 24 V 1 mA

thermal rated current I_{th} 4 A

Mechanical values and environment

Anfahrsgeschwindigkeit	max. 60 m/min
Approach direction	C
Connection type	
	1 x M16 x 1.5
Number of door position NO contacts	1
Number of door position positively driven contacts	1
Design	short housing
Actuating element	
Slide bearing plastic	Roller arm (d roller = 12 mm)
Actuation frequency	max. 5000 1/h

Actuating force	15 N
Installation orientation	any
Storage temperature	-25 ... 80 °C
Mechanical life	20 x 10 ⁶
Switching principle	Slow-action switching contact
Degree of protection	IP67
Ambient temperature	-20 ... 80 °C

Material

Contact Silver alloy, gold flashed

Housing Reinforced thermoplastic

Characteristic values according to EN ISO 13849-1 and EN IEC 62061

	B10 _D	Mission time
Safe position sensing	2x10 ⁷	20 y
Important! Values valid at DC-13 100 mA/24V		

Miscellaneous

C number
C2069