


A

CDP2 Contactors





Four Pole Definite Purpose Contactors With AC Coil (Open Type only)

Full Load Amps	Locked Rotor Amps			Resistive Amps ②	Maximum Horsepower ②					Catalog Number	Price Each	Std. Pkg.
					1Ø		3Ø					
	240V ②	480V	600V		120V	240V	200V	240V	480V			
30 ❶	180	150	120	40	2	5	10	10	15	CDP2-E4P30A-* ❸	126.63	20
40	240	200	160	50	3	7-1/2	10	10	20	CDP2-E4P40A-* ❸	147.01	20



Series CDP2 4-pole contactor

Auxiliary Contacts for 4 Pole Contactors

Auxiliary	Description	Circuit Diagram	Catalog Number	Price
	Two pole Auxiliary Contact Block (1-NO / 1-NC) - Side mount with quick connect stabs for all 4 pole contactors		CDP2-BE-11	41.85
	One pole Auxiliary Contact Block (SPDT) - Side mount with quick connect stabs for all 4 pole contactors		CDP2-BE-1SPDT	36.93

A.C. Coil Codes

AC Coil Code	Voltage Range
	60 Hz
24	24V
120	120V
220W	208-240V
277	277V
480	480V

Ordering Instructions

Specify Catalog Number	
Replace (*) with Coil Code	See Coil Codes on this page

- ① 25A contactors available by special order. Contact your Sprecher + Schuh representative.
- ② 240V rating also applies to 277V applications.
- ③ Box Power Lugs are supplied as standard. Screw terminals are available on the power connections by special order only in quantity.
- ④ Screw per terminals are supplied standard on 25 and 30A contactors. Box Lugs available by special order only in quantity.