


## CET1-AX-LRA-00-50F-SA-C2333-111918 (Order no. 111918)

### Read head CET1-AX-... M12, with guard locking and guard lock monitoring, escape release and lockout bar

- ▶ Read head with guard locking
- ▶ Locking force up to 6500 N
- ▶ Category 4 / PL e according to EN ISO 13849-1
- ▶ With plug connector M12
- ▶ With escape release, 75 mm long
- ▶ With lockout bar
- ▶ 2 LEDs (1 freely configurable)
- ▶ Approach direction A (delivery state)



#### Approach direction



Horizontal

Can be adjusted in 90° steps

#### Lockout mechanism

The lockout bar can be used to prevent maintenance personnel from being unintentionally locked in the danger zone, for example.

**Important:** The lockout bar is not a safety function..

This device with lockout bar possesses no auxiliary release.

#### Solenoid operating voltage

- ▶ DC 24 V +10%, -15%

#### Guard locking type

CET1 Closed-circuit current principle, guard locking by spring force. Release by applying voltage to the guard locking solenoid.

## LED function display

LED red illuminates when solenoid is switched on

LED green freely configurable

## Notes

- ▶ Special connecting cables from EUCHNER are required for the connection. Please take into account in the order!
- ▶ The read head CET may be operated only in conjunction with the actuator CET-A-BWK-50X. The actuator must be ordered separately.

## Escape release

This is used for manual release of guard locking from the danger zone without tools.

Dimensional drawings

