

TZ2LE024RC18VAB-C2140 (Order no. 102917)

Technical data

Approvals



Operating and display elements

LED display

Operating voltage corresponds to the solenoid voltage
(2 LEDs; green, red)

Electrical connection values

Fuse	max. 4 A gG (>70 °C => 2 A gG)
------	-----------------------------------

Power consumption	10 W
-------------------	------

Rated insulation voltage U_i	50 V
--------------------------------	------

Rated impulse voltage U_{imp}	1.5 kV
---------------------------------	--------

Utilization category

DC-13	4 A 24 V (>70 °C => 2 A)
-------	-----------------------------

AC-15	4 A 50 V (>70 °C => 2 A)
-------	-----------------------------

Solenoid operating voltage

AC/DC	24 V -15% ... +10%
-------	--------------------

Solenoid duty cycle	100 %
---------------------	-------

Switching voltage

min. at 10 mA	12 V
---------------	------

Switching current

min. at 24 V	1 mA
--------------	------

thermal rated current I_{th}	4 A (>70 °C => 2 A)
--------------------------------	------------------------

Mechanical values and environment

Anfahrsgeschwindigkeit	max. 20 m/min
------------------------	---------------

Approach direction

Actuating head left C

Connection type	
1 x	Plug connector RC18 (18 + PE)
Number of door position NO contacts	1
Number of guard lock monitoring NO contacts	2
Number of door position positively driven contacts	3
Number of guard lock monitoring positively driven contacts	2
Extraction force	30 N
Actuation frequency	max. 1200 1/h
Actuating force	35 N
Lid	black
Installation orientation	any
Insertion depth	52 mm
Storage temperature	-25 ... 80 °C
Mechanical life	1 x 10 ⁶
Retention force	10 N
Switching principle	Slow-action switching contact
Degree of protection	IP65
Ambient temperature	-25 ... 80 °C
Material	
Contact	Silver alloy, gold flashed
Housing	Anodized die-cast alloy
Locking force $F_{\max}$	2000 N
Locking force F_{Zh}	1500 N
Guard locking principle	Open-circuit current principle

Characteristic values according to EN ISO 13849-1 and EN IEC 62061

	B10 _D	Mission time
--	------------------	--------------