

**NG1SM-510-MC2064 (Order no. 094186)**

## Technical data

### Approvals



### Electrical connection values

Fuse	max. 6 A gG	
Connection cross section	0.34 ... 1.5 mm <sup>2</sup>	
Rated insulation voltage U <sub>i</sub>	250 V	
Rated impulse voltage U <sub>imp</sub>	2.5 kV	
Utilization category		
	AC-12	10 A 230 V
	AC-15	6 A 230 V
	DC-13	6 A 24 V
Switching current		
	min. at DC 24V	10 mA
thermal rated current I <sub>th</sub>	6 A	

### Mechanical values and environment

Anfahrsgeschwindigkeit	0.5 ... 60 m/min	
Connection type		
	1 x	M20 x 1.5
Number of door position NC contacts	1	
Number of door position NO contacts	1	
Actuating element	Pivoted lever arm (Aluminum rod)	
Actuating force	min. 15 N	
Installation orientation	any	
Storage temperature	-25 ... 80 °C	
Mechanical life	30 x 10 <sup>6</sup>	
Contact bounce time	max. 3 ms	
Switching principle	Snap-action switching contact	

Schließzeit max. 4 ms

Degree of protection IP67

Ambient temperature -25 ... 80 °C

Material

Contact Silver alloy, gold flashed

Housing Anodized die-cast alloy

### Miscellaneous

C number

C2064