

**NG1WO-510L060GE-M (Order no. 090614)**

## Technical data

### Approvals



### Electrical connection values

Fuse	max. 6 A gG
Connection cross section	0.34 ... 0.75 mm <sup>2</sup>
Display module	AC/DC 12 ... 60 ... 60 V LED yellow
Rated insulation voltage $U_i$	250 V
Rated impulse voltage $U_{imp}$	2.5 kV
Utilization category	AC-15 6 A 230 V AC-12 10 A 230 V DC-13 6 A 24 V
Switching current	min. at DC 24V 10 mA
thermal rated current $I_{th}$	6 A

### Mechanical values and environment

Anfahrsgeschwindigkeit	0.01 ... 10 m/min
Connection type	1 x M20 x 1.5
Number of door position NC contacts	1
Number of door position NO contacts	1
Actuating element	Rounded plunger
Actuating force	15 ... 30 N
Installation orientation	any
Storage temperature	-25 ... 80 °C
Mechanical life	30 x 10 <sup>6</sup>

Contact bounce time	max. 3 ms
Switching principle	Snap-action switching contact
Schließzeit	max. 4 ms
Degree of protection	IP67
Ambient temperature	-25 ... 80 °C
Material	
	Contact Silver alloy, gold flashed
	Housing Anodized die-cast alloy