


TK1-528CB048MC2304 (Order no. 110942)

Technical data

Approvals



Electrical connection values

Fuse	max. 4 A gG	
Power consumption	8 W	
Connection cross section	0.34 ... 1.5 mm ²	
Rated insulation voltage U _i	250 V	
Rated impulse voltage U _{imp}	2.5 kV	
Utilization category		
	AC-15	4 A 230 V
	DC-13	4 A 24 V
Solenoid operating voltage		
	AC/DC	48 V -15% ... +10%
Solenoid duty cycle	100 %	
Switching voltage		
	min. at 10 mA	12 V
Switching current		
	min. at 24 V	1 mA
thermal rated current I _{th}	4 A	

Mechanical values and environment

Approach direction	C	
Connection type		
	3 x	M20 x 1.5
Number of guard lock monitoring NO contacts	1	
Number of guard lock monitoring positively driven contacts	1	
Actuation frequency	max. 1200 1/h	

Installation orientation	any
Storage temperature	-30 ... 70 °C
Mechanical life	1 x 10 ⁶
Switching principle	Slow-action switching contact
Degree of protection	IP67
Ambient temperature	-30 ... 55 °C
Material	
	Contact Silver alloy, gold flashed
	Housing Reinforced thermoplastic
Locking force F _{max}	5000 N
Guard locking principle	Closed-circuit current principle

Characteristic values according to EN ISO 13849-1 and EN IEC 62061

	B10 _D	Mission time
Guard lock monitoring	2x10 ⁶	20 y
Important! Values valid at DC-13 100 mA/24V		

	PL	Maximum SIL	Category	Mission time
Control of guard locking	Depending on external control of guard locking			20 y

Miscellaneous

C number	C2304
----------	-------