

MGB-L1HB-EIA-L-159660 (Order no. 159660)

Components



111839

MGB-H-AA1A6-L-111839

Handle module MGB-H... with automatically extending lockout mechanism

- ▶ Intelligent bolt tongue
- ▶ Fold-out lockout mechanism
- ▶ Second automatically extending lockout mechanism
- ▶ Door handle
- ▶ Mounting plate

Technical data

Approvals



Handle modules MGB-H-AA1A6-L-111839 (Order no. 111839)

Mechanical values and environment

| | |
|--------------------------|--|
| Installation orientation | Door hinge DIN left |
| Storage temperature | -25 ... 70 °C |
| Degree of protection | IP65 |
| Ambient temperature | -20 ... 55 °C |
| Material | |
| | Housing Fiber glass reinforced plastic, nickel-plated die-cast zinc, stainless steel |

Miscellaneous

| | |
|------------------------|---|
| Product version number | V3.0.0 |
| Additional feature | with mounting plate and automatic lockout mechanism |

Workspace

| | |
|--------------------------------------|---|
| Secured switch-off distance s_{ar} | |
| Only with sliding door | 20 mm (Only applies for use on sliding doors with deactivated guard lock monitoring) |

Operating and display elements

Occupancy diagram

B1

L1