


TZ1RE024RC18VAB-C2163 (Order no. 099024)

Technical data

Approvals



Operating and display elements

LED display

Operating voltage corresponds to the solenoid voltage
(2 LEDs; green, red)

Electrical connection values

Fuse	max. 4 A gG (>70 °C => 2 A gG)	
Power consumption	10 W	
Rated insulation voltage U_i	50 V	
Rated impulse voltage U_{imp}	1.5 kV	
Utilization category		
	AC-15	4 A 50 V (>70 °C => 2 A)
	DC-13	4 A 24 V (>70 °C => 2 A)
Solenoid operating voltage		
	AC/DC	24 V -15% ... +10%
Solenoid duty cycle	100 %	
Switching voltage		
	min. at 10 mA	12 V
Switching current		
	min. at 24 V	1 mA
thermal rated current I_{th}	4 A (>70 °C => 2 A)	

Mechanical values and environment

Anfahrsgeschwindigkeit	max. 20 m/min
------------------------	---------------

Approach direction

Actuating head on the right A

Connection type	
1 x	Plug connector RC18 (18-pin + PE)
Number of door position NO contacts	1
Number of guard lock monitoring NO contacts	1
Number of door position positively driven contacts	3
Number of guard lock monitoring positively driven contacts	2
Extraction force	30 N
Actuation frequency	max. 1200 1/h
Actuating force	35 N
Lid	black
Installation orientation	any
Insertion depth	52 mm
Storage temperature	-25 ... 80 °C
Mechanical life	1 x 10 ⁶
Retention force	10 N
Switching principle	Slow-action switching contact
Degree of protection	IP65
Ambient temperature	-25 ... 80 °C
Material	
Housing	Anodized die-cast alloy
Contact	Silver alloy, gold flashed
Locking force $F_{\max}$	2000 N
Locking force F_{Zh}	1500 N
Guard locking principle	Closed-circuit current principle

Characteristic values according to EN ISO 13849-1 and EN IEC 62061

	B10 _D	Mission time
--	------------------	--------------