

## KCB4E4E4E4E5678X (Order no. 073967)

### Series KC...

- ▶ Screw terminal
- ▶ 8 actuating directions
- ▶ Bellows for surface mounting (X)



## Technical data

### Approvals



### Electrical connection values

Fuse	T6/F10
Rated insulation voltage $U_i$	250 V
Rated impulse voltage $U_{imp}$	2.5 kV
Utilization category	AC-15 230V 4A DC-13 24V 2A
Switching voltage	min. 10 V
Switching current	(at 24V) min. 12 mA

### Mechanical values and environment

Connection type	Screw terminal
Number of monitoring contacts	max. 4 4 (4 directions x 1 screw element)
Actuating directions	max. 8 max. 3 positions (0-1-2) possible per type and direction
Storage temperature	-25 ... 70 °C
Mechanical life	1 x 10 <sup>6</sup>
Mounting cut-out	Ø 52 mm
Switching principle	Changeover contact C, IEC 947-5-1 (Snap-action contact element, design ES556)
Degree of protection	on the front with bellows IP65 (Version X)
Ambient temperature	-25 ... 65 °C

## Material

	Housing thermoplastic/aluminum
	Switching lever galvanized steel
Contact	Silver alloy
	Bellows elastomer, black (Low PAH)

## Miscellaneous

Additional feature	Bellows X for surface mounting
--------------------	--------------------------------