


MGB-L1HE-ARA-R-157965 (Order no. 157965)

Locking set MGB-L1HE-ARA... (guard locking by spring force) with 1 pushbutton, emergency stop, RC26

- ▶ Guard locking with guard lock monitoring
- ▶ Can be connected in series with other AR devices (e.g. CES-AR and CET-AR)
- ▶ Emergency stop according to ISO 13850
- ▶ 1 illuminated pushbuttons
- ▶ With plug connector RC26
- ▶ With escape release
- ▶ Unicode



Guard locking type

MGB- The locking arm is held in the locked position by spring force and is unlocked by solenoid force
L1... (closed-circuit current principle, mechanically locked).

Door hinge

A mechanical door stop is permanently integrated into the evaluation module of the MGB. A marking on the stop makes adjustment easier.

LED indicator

The LED indicator indicates all important system and status information.

Monitoring outputs

- OD ON when the door is closed
- OT Bolt tongue inserted into the evaluation module
- OL Guard locking solenoid in locked position
- OI Diagnostics; there is a fault

Emergency stop device

S1 2 positively driven contacts and 1 NO contact (e.g. monitoring contact), emergency stop with turn-to-reset, not illuminated


Pushbuttons

S2 1 NO contact, illuminated

Escape release

The escape release enables people shut in to open the guard locked door from the danger zone.

Dimensional drawings



Dimensional drawings

