

PROVO PART NUMBER

6725

**MULTI-CONDUCTOR • FOIL SHIELD
STRANDED TINNED COPPER CONDUCTORS
CONDUCTORS TWISTED • PVC INSULATION
100% ALUMINUM FOIL SHIELD
STRANDED TINNED COPPER DRAIN WIRE
PVC JACKET • -20°C +105°C**



SPEC CRITERIA	SPECIFICATION
AWG	22
STRANDING	7 x 30
NUMBER OF CONDUCTORS	25
DRAIN WIRE AWG	24
INSULATION TYPE	PVC
INSULATION THICKNESS	0.010
JACKET TYPE	PVC
JACKET THICKNESS	0.030
NOM. CABLE OD	0.356
VOLTAGE	600
TEMPERATURE	-20°C to +105°C
PUT-UP METERS	300 / 150
WEIGHT (LBS)	110 / 55
CSA	AWM, CMG, FT-4
UL	CMG, UL444
RoHS	COMPLIANT
FLAME TEST	FT-4
COLOUR CODE	1) Black 2) White 3) Red 4) Green 5) Orange 6) Blue 7) White w/Black 8) Red w/Black 9) Green w/Black 10) Orange w/Black 11) Blue w/Black 12) Black w/White 13) Red w/White 14) Green w/White 15) Blue w/White 16) Black w/Red 17) White w/Red 18) Orange w/Red 19) Blue w/Red 20) Red w/Green 21) Orange w/Green 22) Black/White/Red 23) White/Black/Red 24) Red/Black/White 25) Green/Black/White

©2022 PROVO LTD.

Provo makes every reasonable effort to ensure their accuracy at the time of this publication. Information and specifications herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. The information provided is correct to the best of Provo's knowledge, and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes part of. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. All sales of Provo products are subject to Provo's standard terms and conditions of sale.