

C-M12F08-07X025PV20,0-MA-105071 (Order no. 105071)

Connecting cable with angled plug connector M12, 8-pin, 20 m

- ▶ M12 female plug, 8-pin
- ▶ Angled plug connector
- ▶ PVC cable
- ▶ Cable length 20 m
- ▶ With flying lead



These special connecting cables are needed for the connection of the CET to a CES evaluation unit.

Please take into account in the order!

Interference is prevented by special screening.

Important

Connecting cables are not allowed to be extended.

Notice

The connecting cables with PUR sheath are suitable for drag chains with a minimum bending radius of 60 mm (10 times the cable diameter).

Technical data

Approvals



Electrical connection values

Rated voltage	36 V
Rated voltage	30 V
Nominal current	at 40 °C 2 A
Test voltage	1.5 kV
Individual shielding	yes, shield around flexes BN and WH connected to pin 3, coverage approx. 85%
Degree of contamination according to EN 60664-1	3

Mechanical values and environment

Conductor identification	Color code
Conductor cross-section	0.25 mm ²
Number of conductors	7
Static bending radius	10 x cable diameter
Storage temperature	-40 ... 80 °C
Cable outlet	Angle
Cable type	straight
Cable diameter	approx. 5.8 mm
Cable length	20 m
Sheath color	black
Drag chain suitability	No
Silicone-free	Yes
Cable ambient temperature (dynamic)	5 ... 80 °C
Cable ambient temperature (static)	-40 ... 80 °C

Material	
Conductor	Cu
Sheath	PVC

Connection 2

Conductor end	Sheath stripped
Connection type	flying lead

Connection 1

Connection type	M12
Connection type	Female plug
Tightening torque	0.5 Nm
Number of pins	8
Degree of protection	IP67
Plug lock	Screw connection

Material

Plug housing	TPU, self-extinguishing
Plug lock	CuZn, nickel plated