C-MINF12-12X1,0PV03,6-MA-100960 (Order no. 100960)

Connecting cable with plug connector MR12, 12-pin, 3.6 m

- MR12 female plug, 12-pin
- Straight plug connector
- PVC cable
- Cable length 3.6 m
- With flying lead

Connector assignment

1	OG
2	BU
3	WH/BK
4	RD/BK
5	GN/BK
6	OG/BK
7	BU/BK
8	BK/WH
9	GN/YE
10	RD
11	WH
12	BK

Dimensional drawings

Dimension AØ 32 Dimension B64 Dimension CØ 9.8

Technical data

Approvals

c UL us LISTED

Electrical connection values

Rated voltage	300 V

Mechanical values and environment

Conductor cross-section	18 AWG
Number of conductors	12
Storage temperature	-40 ... 80 °C
Cable type	straight
Cable diameter	
approx.	10.4 mm
Cable length	3.6 m
Drag chain suitability	No
Ambient temperature	-40 ... 80 °C
Material	
Sheath	PVC
	Connection 2
Conductor end	Sheath stripped
Connection type	flying lead
	Connection 1
Connection type	Plug connector BHA12
Connection type	Female plug
Cable outlet	straight
Number of pins	12
Degree of protection	IP67
Plug lock	Screw connection

Material

Plug lock	Plastic