

RIEGEL CES-AR-C/F (Order no. 104964)

Bolt for safety switch CES-C01

- ▶ Bolt for switch CES-C01
- ▶ Steel bolt
- ▶ For doors hinged on the left or right
- ▶ Bolt with escape lever
- ▶ Detent knob in open position
- ▶ Ball detent mechanism in closed position
- ▶ Suitable for a door gap of approx. 15 mm
- ▶ Protective plate for safety switch



Scope of delivery

- ▶ CES actuator pre-assembled in the bolt tongue
- ▶ Protective plate for safety switch pre-assembled

To be ordered separately:

- ▶ Safety switch

Latching in closed position

Bolt latches in closed position and prevents unintentional opening of the bolt. Ball or spring detent mechanisms are opened by overcoming the spring force.

Door types and door hinges

Suitable for hinged or sliding doors Suitable for doors hinged on the left and right With door stop, door cannot be opened inwards.

Escape release

Bolts with escape release feature an escape lever enabling the bolt to be opened from inside a guard.

Protective plate

The protective plate protects the switch against damage.

Integrated lockout bar

With the aid of the integrated lockout bar, the bolt can be secured in the open position, e.g. using padlocks. It is possible to prevent people from being locked in the danger area unintentionally.

Technical data

Mechanical values and environment

Approach direction	A or C
Number of safety switches that can be mounted	1
Escape release	Yes
Storage temperature	-25 ... 70 °C
Material	
Guide strips	Plastic
Base plate	Galvanized steel
Switch bracket	Steel powder-coated
Handle	Plastic

Miscellaneous

Detent mechanism closed position	Ball detent mechanism
Detent mechanism open position	Bolt detent mechanism