

KCB2B002A000000W (Order no. 094745)

Series KC...

- ▶ Screw terminal
- ▶ 2 actuating directions
- ▶ Bellows for panel mounting (W)



Technical data

Approvals



Electrical connection values

Fuse	T6/F10
Rated insulation voltage U_i	250 V
Rated impulse voltage U_{imp}	2.5 kV
Utilization category	
	DC-13 24V 2A
	AC-15 230V 4A
Switching voltage	min. 10 V
Switching current	
	(at 24V) min. 12 mA

Mechanical values and environment

Connection type	Screw terminal
Number of monitoring contacts	max. 5 5 (1 direction x 3 switching elements, 1 direction x 2 switching elements)
Actuating directions	max. 2 max. 3 positions (0-1-2) possible per type and direction
Storage temperature	-25 ... 70 °C
Mechanical life	1 x 10 ⁶
Mounting cut-out	Ø 52 mm
Switching principle	Changeover contact C, IEC 947-5-1 (Snap-action contact element, design ES556)
Degree of protection	
	on the front with bellows IP65 (Version W)
Ambient temperature	-5 ... 65 °C

Material

Contact	Silver alloy
	Housing thermoplastic/aluminum
	Bellows elastomer, black
	(Low PAH)
	Switching lever galvanized steel

Miscellaneous

Additional feature	Bellows W for panel mounting
--------------------	------------------------------