

C-M27F26-PU10,0-MA-111999 (Order no. 111999)

Connecting cable with plug connector RC26, 26-pin, 10 m

- ▶ M27 female plug (RC26), 26-pin
- ▶ Straight plug connector
- ▶ TPE-U cable
- ▶ Cable length 10 m
- ▶ With flying lead
- ▶ Cores numbered, black



Technical data

Electrical connection values

Rated voltage	DC	74 V
Nominal current		4 A

Mechanical values and environment

Conductor identification		Numeric code
Conductor cross-section		23x 0.5 mm ² + 3x 1 mm ²
Dynamic bending radius		10x cable diameter
Halogen-free		Yes
Storage temperature		-25 ... 80 °C
Cable type		straight
Cable diameter		
	approx.	11.5 mm
Cable length		10 m
Sheath color		Window gray RAL 7040
Drag chain suitability		Yes
Cable ambient temperature (dynamic)		-25 ... 80 °C
Cable ambient temperature (static)		-25 ... 80 °C
Material		
	Conductor	EL-Cu flexible wire, bare, super fine strands
	Conductor insulation	TPE
	Sheath	PUR

Connection 2

Conductor end	Sheath stripped
Connection type	flying lead

Connection 1

Connection type	Plug connector M27
Connection type	Female plug
Plug connector designation	RC
Cable outlet	straight

Number of pins 26
(23+3)

Degree of protection IP65
(locked)

Plug lock Screw connection

Insertion cycles 50

Material

Plug housing CuZn, nickel plated

Plug lock CuZn, nickel plated