

## LCA-4TR-M-14-460-AP-156591 (Order no. 156591)

### Light curtain LCA-4TR-M-14-460

- ▶ Light curtain master
- ▶ For cascading (series connection)
- ▶ Resolution 14 mm
- ▶ Protective field height 460 mm
- ▶ Range 6 m
- ▶ With plug connector M12
- ▶ 2 safety outputs (OSSD)
- ▶ Installation material is included with the product




### Protective function



Finger protection

### Cascading (series connection)



Following combinations are possible:

Variant A: Master–slave 2–slave 1

Variant B: Master–slave 1

### LED function display



Transmitter



Receiver

- LED OK                Normal operation
- LED ERROR         Error
- LED STOP           Stop
- LED TEST            Test function
- LED START          Start/restart
- LED SIGNAL LOW   Weak signal

### Connector assignment, transmitter

Plug connector (view of connection side)	Pin	Designation	Function	Connecting cable conductor coloring
	1	24 V DC	Operating voltage, 24 V DC	BN
	2	RANGE 0	Device configuration, corresponds to the standard EN 61131-2	WH
	3	0 V DC	Operating voltage, 0 V DC	BU
	4	RANGE 1	Device configuration, corresponds to the standard EN 61131-2	BK
	5	FE	Functional earth (must be connected to meet the EMC requirements)	GY

## Connector assignment, receiver

Plug connector (view of connection side)	Pin	Designation	Function	Connecting cable conductor coloring
	1	FO1A	Safety output, channel 1	WH
	2	24 V DC	Operating voltage, 24 V DC	BN
	3	FO1B	Safety output, channel 2	GN
	4	K1_K2/ RESTART	Feedback external contactors	YE
	5	SEL_A	Device configuration	GY
	6	SEL_B	Device configuration	PK
	7	0 V DC	Operating voltage, 0 V DC	BU
	8	FE	Functional earth (must be connected to meet the EMC requirements)	RD