

TZ2RE024MVAB-C2082 (Order no. 103754)

Technical data

Approvals



Operating and display elements

LED display

Operating voltage corresponds to the solenoid voltage
(2 LEDs; green, red)

Electrical connection values

Fuse	max. 4 A gG ($>70\text{ °C} \Rightarrow 2\text{ A gG}$)
------	--

Power consumption	10 W
-------------------	------

Connection cross section	0.34 ... 1.5 mm ²
--------------------------	------------------------------

Rated insulation voltage U_i	250 V
--------------------------------	-------

Rated impulse voltage U_{imp}	2.5 kV
---------------------------------	--------

Utilization category

DC-13	4 A 24 V ($>70\text{ °C} \Rightarrow 2\text{ A}$)
-------	--

AC-15	4 A 230 V ($>70\text{ °C} \Rightarrow 2\text{ A}$)
-------	---

Solenoid operating voltage

AC/DC	24 V -15% ... +10%
-------	--------------------

Solenoid duty cycle	100 %
---------------------	-------

Switching voltage

min. at 10 mA	12 V
---------------	------

Switching current

min. at 24 V	1 mA
--------------	------

thermal rated current I_{th}	4 A ($>70\text{ °C} \Rightarrow 2\text{ A}$)
--------------------------------	---

Mechanical values and environment

Anfahrsgeschwindigkeit	max. 20 m/min
------------------------	---------------

Approach direction

Actuating head on the right A

Connection type	
	1 x M20 x 1.5
Number of door position NO contacts	1
Number of guard lock monitoring NO contacts	2
Number of door position positively driven contacts	3
Number of guard lock monitoring positively driven contacts	2
Extraction force	30 N
Actuation frequency	max. 1200 1/h
Actuating force	35 N
Lid	black
Installation orientation	any
Insertion depth	52 mm
Storage temperature	-25 ... 80 °C
Mechanical life	1 x 10 ⁶
Retention force	10 N
Switching principle	Slow-action switching contact
Degree of protection	IP65
Ambient temperature	-25 ... 80 °C
Material	
	Contact Silver alloy, gold flashed
	Housing Anodized die-cast alloy
Locking force $F_{\max}$	2000 N
Locking force F_{Zh}	1500 N
Guard locking principle	Open-circuit current principle

Characteristic values according to EN ISO 13849-1 and EN IEC 62061

	B10 _D	Mission time
Monitoring of the guard position	3x10 ⁶	20 y