

## SN03X16-772L-M (Order no. 088416)

### Series SN... 16 mm, inductive

- ▶ Proximity switch spacing 16 mm
- ▶ Upright housing, small flange
- ▶ Degree of protection IP67 according to IEC 60529
- ▶ LED function display




### Rated operating distance

With 16 mm proximity switch spacing, the rated operating distance is 5 mm.

### LED function display

DC and AC switching elements are equipped as standard with a function display on the switching element (yellow). The function display can be seen from the exterior.

### Dimensional drawings



1 Operating distance


1) Dimension only applies for steel. With ferrite dogs operating distance 0.2-0.7

2 Actuator

3 LED

4 4 Number of stations

Connection examples



## Technical data

### Approvals



### Workspace

Rated operating distances $S_n$	5 mm
Assured operating distances $S_a$	0 ... 4 mm (Dimension applies only to steel (ST37) and to EUCHNER trip dogs of series UX../GX..)
Switching hysteresis	max. 0.5 mm
Repeat accuracy R	5 %

### Operating and display elements

LED display	Yes
-------------	-----

### Electrical connection values

Connection cross section	0.34 ... 1.5 mm <sup>2</sup> (Screw terminals)
Output type	PNP
Rated operating current $I_e$	250 mA
Rated insulation voltage $U_i$	60 V
Operating voltage	DC 10 ... 55 V
EMC protection requirements	EN IEC 60947-5-2
Utilization category	DC-12 DC-13 (The output is to be protected with a free-wheeling diode for inductive loads.)
Short circuit and overload protection, pulsed	Yes
No-load current $I_0$	15
Off-state current $I_r$	max. 0.001 mA