

SN02R16-502LE060-M (Order no. 088762)

Series SN... 16 mm, mechanical

- ▶ Plunger spacing 16 mm
- ▶ Upright housing, small flange
- ▶ Degree of protection IP67 according to IEC 60529
- ▶ LED function display



Switching element





ES 502 E Snap-action switching contact 1 NC + 1 NO

LED function display

Function display is available for the following voltage range

LE060 12 ... 60 V AC/DC

Dimensional drawings



4	84
3	72
2	48
n	L
Anzahl der Stößel	
⑤	

1 Operating point

2 Free position


3 Dog

4 LED

5 n Number of plungers

Connection examples

ES 502 E



Technical data

Approvals



Electrical connection values

Fuse	max. 8 A gG	
Connection cross section	0.34 ... 1.5 mm ²	
Display module	AC/DC	12 ... 60 ... 60 V LED
Rated insulation voltage U _i	250 V	
Rated impulse voltage U _{imp}	2.5 kV	
Utilization category	DC-13	6 A 24 V
	AC-15	6 A 230 V
	AC-12	8 A 250 V
Switching current	min. at DC 12V	min. 10 mA
thermal rated current I _{th}	8 A	

Mechanical values and environment

Anfahrsgeschwindigkeit	0.01 ... 80 m/min	
Connection type	2 x	M20 x 1.5
Number NC contacts	2	
Number of switching elements	2	
Number of NO contacts	2	
Design	upright	
Actuating element	Slide bearing	Roller plunger
	(Operating point accuracy ± 0.01. The reproducible operating point accuracy	